

PHASE 1: REMOVE EXISTING WATER FROM YOUR PLUMBING LINES AND WATER HEATER

- 1 Turn water panel dials to the "POWERFILL" position (as noted on front of panel).



- 2 Open low point and fresh water drains under the RV to drain water from lines. Turn on a faucet inside to assist with drainage.



- 3 With a 1-1/8" socket, remove the drain plug from water heater and let water drain.



- 4 Once water has drained from the lines, turn water panel dials so they are at a 45 degree angle and use the "City Water" inlet to blow out the lines (40 PSI max).

NOTE: Close low point drains when complete.



Product information is as accurate as possible as of the date of publication of this flyer (REV 2—9.30.21). Please reference the Alliance RV Owners Guide, available to download at www.AllianceRV.com, for more detailed instructions on the operation of your Alliance RV.

PHASE 2: ADDING WINTERIZING SOLUTION

- A Turn water panel dials to "WINTERIZE" position.

- B Connect short section of garden hose to the "CITY WATER" inlet and the other end in the winterizing solution.

- C Turn the "PUMP" switch on, and the winterizing solution should begin to flow.



- D Open one plumbing fixture at a time until you see the winterizing solution come through. Continue this process for each plumbing fixture, including washer/dryer, dishwasher, and icemaker prep lines, making sure to do both hot and cold lines. (NOTE: When finished pour some additional winterizing solution in any p-trap drains)



- E Once winterizing solution has made its way through all of the plumbing fixtures turn off the "PUMP" switch and disconnect hose from the "CITY WATER" inlet.